

# Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

AGR-6106-S

AGR-6109-S

Single line Analog phone



- Single line analog phone.
- Hearing aid support
- Full duplex speakerphone.
- Message waiting indicator.
- 6 or 9 customizable service dials.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





# **AEi-Corporate Office**

Carrollton, Texas, U.S.A Sales: +1.254.3350555 sales@aeicommunications.com

### AEI-EMEA Office

London, United Kingdom Sales: +44 (0)1753.643736 emea@aeicommunications.com

# **AEi-Asia Pacific Office**

New Taipei City, Taiwan Sales: +886.2.26968809 asiapac@aeicommunications.com

### AEi-CEE&CIS Office

Sales: +382 69 891 251 eastern.europe@aeicommunications.com

Budva, Montenegro

**AEi-Corporate Office** 

so.asia@aeicommunications.com

Penang, Malaysia Sales: +604.3994341

## 1. Features

Keys (0~9, \*, #) Dial keys N/A Line keys

> Function keys Speaker, Volume up/down, 6 or 9 programmable service keys

Phone Features Single line telephone system with speakerphone

Adjustable High-low ringer (2 way selectable switch)

8 steps speakerphone digital volume control

4 steps handset digital volume control

6 non volatile one-touch programmable speed dial memory button

Tone dialing only

Hearing Aid Receiver Compliant

PBX / Standard Line compatible

Multi Purpose LED indicator for Message Waiting and Incoming Ring

# **Hardware Specifications**

Power Line Power (without AC adaptor or battery)

Ring Voltage 40V RMS minimum RJ11 PSTN jack x 1 Jacks

Size and Weight Dimensions: 191mm(L) x 110mm(W) x 106mm(H), Weight: 576g

3. Regulatory EU USA

> FCC Part 68 **PSTN EMI** FCC Part 15B EN55032 & EN55024 EN60950-1

RoHS Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

Telecom TIA/EIA 968-B compliant

Temperature Storage: Low temperature at -10°C High temperature at +60°C

> Operating Low temperature at +5°C High temperature at +35°C

Model:

AGR-6106-S

AGR-6109-S





