

AKD-5103

AKD-5203

1 or 2 Lines  
Analog Phone



- 1 or 2 lines analog phone.
- 3 customizable service dials.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

	Keys	5203	5103
	<ul style="list-style-type: none"> <li>Dial keys</li> <li>Line keys</li> <li>Function keys</li> </ul>	(0~9, *, #) Line1, Line2 with red/green color LED Flash, Volume up/down, Hold, Redial, 3 speed dial keys	(0~9, *, #) N/A Flash, Volume up/down, Redial, 3 speed dial keys
Phone Features	<ul style="list-style-type: none"> <li>One or Two Lines</li> <li>Red color message waiting indicator for ringing and message waiting</li> <li>Handset volume control</li> <li>Ringer volume switch</li> </ul>		<ul style="list-style-type: none"> <li>3 programmable speed dials</li> <li>Selectable flash timing 100ms, 300ms and 600 ms (by hardware setting, default is 600 ms)</li> <li>Redial last call</li> </ul>

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>Line keys and Message waiting indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>Telephone line powered</li> </ul>
Ring Voltage	<ul style="list-style-type: none"> <li>40V RMS minimum</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ14 PSTN jack x 1 ,RJ9 Handset jack x1</li> </ul>
Line cord	<ul style="list-style-type: none"> <li>10 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions:224mm(L) x108mm(W) x 128mm(H), Weight: 745g</li> </ul>

## 3. Regulatory

	USA	EU
PSTN	FCC Part 68	
EMI	FCC Part 15B	EN55032 & EN55024 EN60950-1
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Telecom	<ul style="list-style-type: none"> <li>TIA/EIA 968-B compliant</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>

**Model:**

**AKD-5103**

**AKD-5203**

