

# Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

**ALN-5100** 

Single Line Analog Emergency Phone



- Single line analog emergency phone.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





## **AEi-Corporate Office**

Carrollton, Texas , U.S.A Sales: +1.254.3350555 sales@aeicommunications.com

#### **AEI-EMEA Office**

London, United Kingdom Sales: +44 (0) 1753.643736 emea@aeicommunications.com

## **AEi-Asia Pacific Office**

New Taipei City, Taiwan Sales: +886.2.26968809 asiapac@aeicommunications.com

#### AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

## **AEi-Corporate Office**

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

# 1. Features

Keys • Function keys Volume up/down

Phone Features

- Red color message waiting indicator for ringing and message waiting
- Handset volume control

- Ringer volume switch
- Selectable flash timing 100ms, 300ms and 600 ms (by hardware setting, default is 600 ms)

High temperature at +35°C

## 2. Hardware Specifications

LED Indications

Message waiting indicator

Power

Telephone line powered

Ring Voltage

40V RMS minimum

Jacks

RJ14 PSTN jack x 1 ,RJ9 Handset jack x1

Operating Low temperature at +5°C

Line cord

10 feet x 1

Size and Weight

Dimensions:224mm(L) x108mm(W) x 128mm(H), Weight: 745g

3.	Regulatory	USA	EU
	PSTN	FCC Part 68	
	EMI	FCC Part 15B	EN55032 & EN55024 EN60950-1
	RoHS	<ul> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
	Telecom	TIA/EIA 968-B compliant	
	Temperature	<ul> <li>Storage: Low temperature at -10°C</li> </ul>	High temperature at +60°C

Model:

ALN-5100



