

AMT-9110-SM

AMT-9210-SM

1 or 2 Lines
Corded
Analog Phone



- 1 or 2 lines corded analog phone.
- Full duplex speakerphone.
- Pair up to 4 cordless remotes.
- 10 customizable service dials.
- Message waiting indicator.
- Customizable hotel logo and service dials.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

	Keys	6210	6110
	<ul style="list-style-type: none"> Dial keys Line keys Function keys 	(0~9, *, #) Line1, Line2 with red/green color LED Hold, Redial, Conference, Mute, Speaker, Message, Volume up/down, 10 Service dial keys	(0~9, *, #) N/A Redial, Flash, Mute, Speaker, Message, Volume up/down, 10 Service dial keys
Phone Features	<ul style="list-style-type: none"> One or Two Lines Message key with message waiting indicator 3-Way Conference(9210 only) Call Hold and resume(9210 only) Mute and unmute 		<ul style="list-style-type: none"> 10 programmable service dials Selectable flash timing (9110 only) Speaker and ringer volume control Redial last call Red color message waiting indicator for ringing and message waiting
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9)10Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 		<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 17 dBm

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> Line keys, Conf/Hold, Mute, Speaker keys, and Message waiting indicator
Power	<ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9 V / 1A
Jacks	<ul style="list-style-type: none"> RJ14 PSTN jack x 1, DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	<ul style="list-style-type: none"> 10 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions:227mm(L) x158mm(W) x 142mm(H) , Weight: 950g

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN301406
EMI	FCC Part 15B	EN300386
SAR		EN62479
Safety		EN60950-1
EMC		EN301489-1/6
PSTN	FCC Part 68	
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

AMT-9110-SM

AMT-9210-SM

AMT-9110-SM-79

AMT-9210-SM-79

