

SMT-9110-SM

1 or 2 Line  
Corded SIP  
Phone

SMT-9210-SM



- 1 or 2 lines corded SIP phone.
- Full duplex speakerphone.
- 10 customizable service dials.
- Pair up to 4 cordless remotes.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

**AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



## 1. Features

Keys	9210	9110
	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2 with red/green color LED</li> <li>Function keys Conference, Hold, Redial, Mute, Speaker, Message, Volume up/down, 10 Service dial keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>NA</li> <li>Hold, Redial, Mute, Speaker, Message, Volume up/down, 10 Service dial keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>One or Two Lines</li> <li>Message key with message waiting indicator</li> <li>3-Way Conference(9210 only)</li> <li>Call Hold and resume</li> <li>Mute and unmute</li> </ul>	<ul style="list-style-type: none"> <li>10 programmable service dials</li> <li>Handset, Speaker and ringer volume control</li> <li>Redial last call</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>
Display Contents	<ul style="list-style-type: none"> <li>Talking time</li> <li>IP Address</li> <li>MAC Address</li> </ul>	<ul style="list-style-type: none"> <li>SIP Register Status</li> <li>Firmware Version</li> <li>Failed Network link Warning</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>Web GUI</li> <li>Auto provisioning via TFTP</li> <li>Phone remote resetting</li> </ul>	<ul style="list-style-type: none"> <li>Firmware upgrade via TFTP</li> <li>Phone status monitoring system</li> </ul>
Codec	<ul style="list-style-type: none"> <li>G.711 (a-law, <math>\mu</math>-law)</li> </ul>	
Network Protocol	<ul style="list-style-type: none"> <li>HTTP server</li> <li>ToS / VLAN IEEE 802.1 p/q</li> </ul>	<ul style="list-style-type: none"> <li>Static IP, DHCP Client</li> </ul>
SIP Security	<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> <li>Web login authentication for web setup</li> <li>MD5 for SIP authentication (RFC 2069/ RFC2617)</li> </ul>	<ul style="list-style-type: none"> <li>HTTPS</li> <li>TLS 1.2</li> </ul>
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality	<ul style="list-style-type: none"> <li>CNG: Comfortable noise generator</li> <li>Echo canceller: LEC / AEC</li> <li>Jitter buffer/PLC</li> </ul>	
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>	
DECT Standard	<ul style="list-style-type: none"> <li>DECT / CAT iq 2.0 compatible</li> <li>Radio Frequency Range : 1880~1930 MHz</li> <li>EU : 1881.792(ch0)~1897.344(ch9) 10 Channels</li> <li>US : 1921.536(ch0)~1928.448(ch4) 5 Channels</li> <li>JP : 1895.616(ch0)~1902.528(ch4) 5 Channels</li> </ul>	<ul style="list-style-type: none"> <li>Channel Space : 1728 KHz</li> <li>Bit rate : 1150 Kbit/s</li> <li>Modulation : GFSK</li> <li>Voice coding : 16 Kbit/s</li> <li>RF power : 17 dBm</li> </ul>

## 2. Hardware Specifications

Display	● 16 x 2 dot matrix LCM with backlight
LED Indications	● Line keys, Conf/Hold, Mute, Speaker keys, and Message waiting indicator
Power	● PoE : IEEE 802.3af compliant ● AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)
Jacks	● RJ45 10/100 Mbs: LAN port x 1; DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	● 9 feet x 1
Size and Weight	● Dimensions:227mm(L) x158mm(W) x 141mm(H), Weight: 905g

## 3. Regulatory

	USA	EU
RF	FCC Part 15D	EN301406
EMI	FCC Part 15B	EN300386
SAR		EN62479
Safety		EN60950-1
EMC		EN301489-1/6
RoHS	● Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	● Storage: Low temperature at -10°C	High temperature at +60°C
	● Operating Low temperature at +5°C	High temperature at +35°C

**Model:**

**SMT-9110-SM-9901**

**SMT-9210-SM-9901**

**SMT-9110-SM-9901TI**

**SMT-9210-SM-9901TI**

